

CRUSHPROOF TUBING

Adapters provide the right size and shape to make sure that your exhaust system is capturing all the fumes properly and improves hose life by ensuring better heat distribution. All adapters require a loose fit over the pipe, and a minimum of 1/2" gap of clearance is required for proper performance. A hook and chain is the standard connection method and the optional suction cup (shown right) works for flush-mounted setups and fits most adapters. Just add "SC" at the end of the adapter number.





F700

7" round with snaps to make it smaller. Fits 3" and 4" hose. This is a must-have item for every garage.



F575

Oval adapter for wide or twin pipes. Roughly 3" x 8" wide. Will work for pipes 2.5" x 7.5" or smaller. Fits 3" and 4" hose.



F1550

Our largest oval adapter is 3" x 15.5" wide. Works with pipes 2.5" x 15" or smaller. Fits 3" and 4" hose.



3" x 11" oval adapter for extra wide setups. Will work with pipes 2.5" x 10.5" or smaller. Fits 3" and 4"

hose



Wire Hose Adapter

Adapt a fabric and wire hose into a Crushproof[®] one! Tapered end clamps to your hose so you can use our adapters and fittings.



F475

Oval adapter for wide or twin pipes. Roughly $3" \times 6"$ wide. Will work for pipes 2.5" x 5.5" or smaller. Fits 3" and 4" hose.



F450 / F400 / F350 / F300 / F250

Round adapters work with straight pipes that are at least 1/2" smaller in diameter than the adapter opening Part numbers designate true ID, so F450 is 4.5" while F300 is 3.0". Hose fit guide: **FLT200:** F250. **FLT250:** F250, F300. **FLT300:** F250, F300, F350. **FLT400:** F350, F400, F450



RA300 & RA250

5" bell adapter with snaps for an adjustable fit on a wide variety of pipes. RA300 fits 2" & 3" hose. RA250 fits 3.5" and 2.5" hose.

G CRUSHPROOF TUBING COMPANY

Phone: 800-654-6858 or 419-293-2111 Fax: 419-293-2609 Email: contact49@crushproof.com Location: 100 North Street McComb, Ohio 45858 crushproof.com

OR SCAN THE QR CODE FOR DIRECT ACCESS TO OUR WEBSITE

